

YG-1 CO., LTD.

HEAD OFFICE

13-40, Songdogwahak-ro 16beon-gil, Yeonsu-gu, Incheon 21984, South Korea


Phone: +82-32-526-0909

www.yg1.solutions

E-mail: yg1@yg1.solutions

Note The information is provided for reference only. Tool specifications are subject to change without prior notice.
Although we endeavor to supply accurate and timely information, there can be no guarantee to cover every particular application.
YG-1 or publishers are not liable for any damage for use of the information.

YouTube **f** **in** **we** **X** **ig**
Search 'YG-1' on social media outlets



YG1YEAP2507004

YG


ALU-POWER
SOLID CARBIDE END MILLS

- Excellent Machining Results with Nonferrous Materials such as Aluminum
- Extremely Sharp Cutting Edges for Lowest Cutting Forces and Increased Tool Life
- Mirror-Like Flute Surface improving Chip Evacuation


EXPANSION Maximize machining efficiency with a variety of length of cut

Up to 2xD
Up to 3xD
Up to 4xD
Up to 5xD
Up to 6xD
Up to 7xD

* For illustration only.
Tools with higher L/D ratios are available.




- Excellent Cutting Performance in Nonferrous Materials like Aluminum due to mirror shine polished chip flutes and razor-sharp cutting edges
- Increased Tool Life and Higher Cutting Accuracy in the types of Aluminum prone to build-up edges
- The ultra fine grain carbide provides the edge integrity necessary for Excellent Surface Finishes
- Sophisticated flute design provides superior Chip Evacuation




Razor-sharp Cutting Edge

Extremely Sharp cutting edges minimize build-up edges and enable highest surface quality




Mirror Shine Flute Polish

Optimal chip evacuation




Symmetrical design

Balanced by symmetrical design allows highest cutting speeds with 2 and 3-Fluted series



Cutting Edge Design

Vibration dampening due to the active suppression of harmonics with radial land




Micro Grain Carbide

Premium carbide substrate provides exceptional wear resistance


CASE STUDY

TEST 1 Ø10 - 2 Flute Square 45° Helix End Mill



Slotting Application



ALU-POWER



Competitor A




Competitor B




Tool	2 Flute Square, 45° Helix
Size	Ø10 x Ø10 x 27 x 75
Work Material	AL6061
RPM	7,500 rev./min.
Feed	1,750 mm/min.
Cutting Depth	3 mm (Axial)
Coolant	Wet Cut
Milling Method	Slotting
Machine	Machining Center

TEST 2 Ø10 - 3 Flute Square 45° Helix End Mill




Down & Side Cutting Application



ALU-POWER



Competitor A



Competitor B



Tool	3 Flute Square, 45° Helix
Size	Ø10 x Ø10 x 27 x 75
Work Material	AL6061
RPM	7,500 rev./min.
Feed	2,500 mm/min.
Cutting Depth	20 mm (Axial) x 0.15 (Radial)
Coolant	Wet Cut
Milling Method	Down & Side Cutting
Machine	Machining Center

GUIDE TO ICONS



Tool Material



Chamfer Angle



Helix Angle



Tolerance of Ball Radius



Type of Periphery



Plain Shank (with DIN Standard)



Flat Shank (with DIN Standard)



No. of Flutes



Cutting Condition Pages



SELECTION
GUIDE



Please visit
globalyg1.com/mat
for material search

SOLID CARBIDE
ALU POWER
END MILLS

Razor-Sharp Cutting Edges for Soft
and prone to Build-up Edge Materials

◎ : Excellent ○ : Good

Recommended cutting conditions : p. 27

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment		HB	HRc			
P	1	Non-alloy steel	About 0.15% C	Annealed	125				
	2		About 0.45% C	Annealed	190	13			
	3		About 0.45% C	Quenched & Tempered	250	25			
	4		About 0.75% C	Annealed	270	28			
	5		About 0.75% C	Quenched & Tempered	300	32			
	6	Low alloy steel		Annealed	180	10			
	7			Quenched & Tempered	275	29			
	8			Quenched & Tempered	300	32			
	9			Quenched & Tempered	350	38			
	10	High alloyed steel, and tool steel		Annealed	200	15			
	11			Quenched & Tempered	325	35			
M	12	Stainless steel	Ferritic / Martensitic	Annealed	200	15			
	13		Martensitic	Quenched & Tempered	240	23			
	14		Austenitic		180	10			
K	15	Grey cast iron	Pearlitic / ferritic		180	10			
	16		Pearlitic (Martensitic)		260	26			
	17	Nodular cast iron	Ferritic		160	3			
	18		Pearlitic		250	25			
	19	Malleable cast iron	Ferritic		130				
	20		Pearlitic		230	21			
N	21	Aluminum-wrought alloy	Not Curable		60		◎	◎	◎
	22		Curable Hardened		100		◎	◎	◎
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable		75		◎	◎	◎
	24		≤ 12% Si, Curable Hardened		90		◎	◎	◎
	25		> 12% Si, Not Curable		130		○	○	○
	26	Copper and Copper Alloys	Cutting Alloys, PB>1%		110		○	○	○
	27		CuZn, CuSnZn (Brass)		90		○	○	○
	28	Bronze / Brass	CuSn, lead-free copper and electrolytic copper		100		○		○
	29		Duroplastic, Fiber Reinforced Plastic						
	30	Non Metallic Materials	Rubber, Wood, etc.						
S	31	Heat Resistant Super Alloys	Fe Based	Annealed	200	15			
	32			Cured	280	30			
	33			Annealed	250	25			
	34		Ni or Co Based	Cured	350	38			
	35			Cast	320	34			
	36	Titanium Alloys	Pure Titanium		400 Rm				
	37		Alpha + Beta Alloys	Hardened	1050 Rm				
H	38	Hardened steel			550	55			
	39				630	60			
	40	Chilled Cast Iron	Cast		400	42			
	41	Hardened Cast Iron	Hardened		550	55			

SERIES	E5910	E5908	E5909
FLUTE	2	3	2
HELIX ANGLE	50°	40°	30°
CUTTING EDGE SHAPE	BALL NOSE	BALL NOSE	CORNER RADIUS
SIZE MIN	R3.0	R1.0	D4.0
SIZE MAX	R10.0	R8.0	D20.0
PAGE	P6	P7	P8
	NECK	NECK	NECK
	Uncoated	Uncoated	Uncoated



E5930	E5E51	E5E47	E5E48	E5522 E5521	E5E49	E5E50	E5742 E5711	E5E39 E5E40
2	3	1	2	2	3	3	3	3
25°	45°	30°	45°	45°	45°	45°	30°	30°
CORNER RADIUS	CORNER RADIUS	SQUARE	SQUARE	SQUARE	SQUARE	SQUARE	ROUGHING	ROUGHING
D2.0	D3.0	D2.0	D1.0	D3.0	D1.0	D1.0	D6.0	D6.0
D20.0	D20.0	D12.0	D20.0	D20.0	D20.0	D20.0	D25.0	D20.0
P9	P10	P11	P12	P13	P15	P22	P25	P26
NECK	LONG LENGTH	-	SHORT LENGTH	LONG LENGTH	LONG LENGTH	NECK	LONG LENGTH	NECK
Uncoated	Uncoated	Uncoated	Uncoated	Uncoated	Uncoated	Uncoated	Uncoated	Uncoated



									1
									2
									3
									4
									5
									6
									7
									8
									9
									10
									11
									12
									13
									14
									15
									16
									17
									18
									19
									20
◎	◎	○	◎	◎	◎	◎	◎	◎	21
◎	◎	○	◎	◎	◎	◎	◎	◎	22
◎	◎	○	◎	◎	◎	◎	◎	◎	23
◎	◎	○	◎	◎	◎	◎	◎	◎	24
○	○	○	○	○	○	○	○	○	25
									26
									27
									28
		◎							29
									30
									31
									32
									33
									34
									35
									36
									37
									38
									39
									40
									41




SOLID CARBIDE ALU-POWER END MILLS
CARBIDE, 2 FLUTE 50° HELIX BALL NOSE with NECK

PLAIN SHANK

E5910 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



Unit : mm

EDP No.	Radius of Ball Nose	Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter
	R(±0.02)	D1	D2	L1	L3	L2	D3
E5910060	R3.0	6.0	6	5.5	25	55	5.4
E5910080	R4.0	8.0	8	7	30	65	7.2
E5910100	R5.0	10.0	10	8.5	35	75	9
E5910120	R6.0	12.0	12	10.5	40	75	11
E5910160	R8.0	16.0	16	14	50	90	14.5
E5910200	R10.0	20.0	20	17	50	100	18

▶ DLC Coatings is available on your request.


Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
±0.020	h5

SOLID CARBIDE ALU-POWER END MILLS
CARBIDE, 3 FLUTE 40° HELIX BALL NOSE with NECK

PLAIN SHANK

E5908 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



Unit : mm

EDP No.	Radius of Ball Nose	Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter
	R(±0.02)	D1	D2	L1	L3	L2	D3
E5908020	R1.0	2.0	6	3	5	60	1.9
E5908025	R1.25	2.5	6	4	6	60	2.4
E5908030	R1.5	3.0	6	4.5	6.5	60	2.8
E5908035	R1.75	3.5	6	5	7	65	3.2
E5908040	R2.0	4.0	6	6	8	65	3.7
E5908050	R2.5	5.0	6	7.5	10	65	4.6
E5908060	R3.0	6.0	6	9	12	75	5.6
E5908080	R4.0	8.0	8	12	25	75	7.4
E5908100	R5.0	10.0	10	15	30	80	9.4
E5908120	R6.0	12.0	12	18	36	90	11.4
E5908160	R8.0	16.0	16	24	40	100	15.4

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
0 ~ - 0.03	h5

◎ : Excellent ○ : Good

ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S						H				
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed		Copper and Copper Alloys (Bronze / Brass)		Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○	○	○	○													

◎ : Excellent ○ : Good

ISO	P										M				K							
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron			
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20		
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21		
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230		
Recommend																						
ISO	N										S						H					
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	
HRc											15	30	25	38	34	36	37	55	60	42	55	
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550	
Recommend	◎	◎	◎	◎	○	○	○															



SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH CORNER RADIUS

PLAIN SHANK

E5E51 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish
- ▶ Reduces chipping of corners




Unit : mm

EDP No.	Corner Radius	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	R	D1	D2	L1	L2
E5E51030	R0.5	3.0	6	12	57
E5E51901	R1.0	3.0	6	12	57
E5E51040	R0.5	4.0	6	15	57
E5E51902	R1.0	4.0	6	15	57
E5E51050	R0.5	5.0	6	20	57
E5E51903	R1.0	5.0	6	20	57
E5E51060	R0.5	6.0	6	20	65
E5E51904	R1.0	6.0	6	20	65
E5E51080	R0.5	8.0	8	22	65
E5E51905	R1.0	8.0	8	22	65
E5E51100	R0.5	10.0	10	25	70
E5E51906	R1.0	10.0	10	25	70
E5E51907	R2.0	10.0	10	25	70
E5E51120	R0.5	12.0	12	25	75
E5E51908	R1.0	12.0	12	25	75
E5E51909	R2.0	12.0	12	25	75
E5E51160	R0.5	16.0	16	35	90
E5E51910	R1.0	16.0	16	35	90
E5E51911	R2.0	16.0	16	35	90
E5E51200	R0.5	20.0	20	40	100
E5E51912	R1.0	20.0	20	40	100
E5E51913	R2.0	20.0	20	40	100

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
0 ~ - 0.015	h5



◎ : Excellent ○ : Good


ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloy steel and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N									S							H				
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials	Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast iron	Hardened Cast iron		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34	55	60	42	55	55	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○																

SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 1 FLUTE

PLAIN SHANK

E5E47 SERIES

- ▶ 1 Flute design allows excellent chip evacuation with plastic and acrylic materials
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish




Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length	Chamfer
	D1	D2	L1	L2	
E5E47020	2.0	3	8	50	0.04
E5E47030	3.0	3	12	50	0.05
E5E47040	4.0	4	15	60	0.07
E5E47050	5.0	5	17	60	0.09
E5E47060	6.0	6	20	65	0.10
E5E47080	8.0	8	22	65	0.14
E5E47100	10.0	10	25	75	0.14
E5E47120	12.0	12	30	80	0.14

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
0 ~ - 0.03	h5



Enforced Cutting Edge

◎ : Excellent ○ : Good

ISO	P											M			K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	25	28	32	36	10	29	32	38	15	35	15	23	10	10	26	3	25	21		
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S						H				
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34	55	60	42	55		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	○	○	○	○	○				◎												




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 2 FLUTE 45° HELIX SHORT LENGTH

PLAIN SHANK

NEW
SIZES

E5E48 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



p.29


* NEW SIZE

Unit : mm


EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E48010	1.0	6	3	50
* E5E48901	1.0	6	6	60
* E5E48015	1.5	6	5	50
* E5E48902	1.5	6	8	60
* E5E48020	2.0	6	6	50
* E5E48903	2.0	6	10	60
* E5E48025	2.5	6	8	55
E5E48030	3.0	6	5	50
E5E48040	4.0	6	8	54
E5E48050	5.0	6	9	54
E5E48060	6.0	6	10	54
E5E48080	8.0	8	12	58
E5E48100	10.0	10	14	66
E5E48120	12.0	12	16	73
E5E48140	14.0	14	18	75
E5E48160	16.0	16	22	82
E5E48180	18.0	18	24	84
E5E48200	20.0	20	26	92

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ - 0.015	h5



Enforced Cutting Edge



◎ : Excellent ○ : Good

ISO	P										M				K								
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21			
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommend																							
ISO	N										S						H						
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	15	30	25	38	40	55		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550		
Recommend	◎	◎	◎	◎	○																		

SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 2 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK



NEW
SIZES

FLAT SHANK

E5522 SERIES

E5521 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



p.29


* NEW SIZE

Unit : mm


EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length	Chamfer
PLAIN	FLAT	D1	D2	L1	L2	
E5522030	E5521030	3.0	6	8	57	0.05
* E5522901	-	3.0	6	11	55	0.05
* E5522902	-	3.0	6	15	65	0.05
E5522040	E5521040	4.0	6	11	57	0.05
* E5522903	-	4.0	6	13	55	0.05
* E5522904	-	4.0	6	16	65	0.05
E5522050	E5521050	5.0	6	13	57	0.05
* E5522905	-	5.0	6	17	55	0.05
* E5522906	-	5.0	6	22	60	0.05
E5522060	E5521060	6.0	6	13	57	0.05
* E5522907	-	6.0	6	17	60	0.05
* E5522908	-	6.0	6	25	70	0.05
* E5522909	-	7.0	8	22	65	0.05
E5522080	E5521080	8.0	8	19	63	0.05
* E5522910	-	8.0	8	22	70	0.05
* E5522911	-	8.0	8	30	80	0.05
E5522100	E5521100	10.0	10	22	7	0.1
* E5522912	-	10.0	10	27	75	0.1
* E5522913	-	10.0	10	35	90	0.1

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ - 0.015	h5



Enforced Cutting Edge



◎ : Excellent ○ : Good

ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S						H				
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast iron	Hardened Cast Iron		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	15	30	55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○																




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 2 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK
NEW SIZES
FLAT SHANK

E5522 SERIES
E5521 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



p.29


* NEW SIZE

Unit : mm

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length	Chamfer
PLAIN	FLAT	D1	D2	L1	L2	
E5522120	E5521120	12.0	12	26	83	0.1
* E5522914	-	12.0	12	32	80	0.1
* E5522915	-	12.0	12	40	95	0.1
E5522140	E5521140	14.0	14	26	83	0.1
* E5522916	-	14.0	14	37	90	0.1
E5522160	E5521160	16.0	16	32	92	0.1
* E5522917	-	16.0	16	42	100	0.1
* E5522918	-	16.0	16	52	110	0.1
E5522180	E5521180	18.0	18	32	92	0.1
* E5522919	-	18.0	18	48	100	0.1
E5522200	E5521200	20.0	20	38	104	0.1
* E5522920	-	20.0	20	48	100	0.1
* E5522921	-	20.0	20	55	110	0.1

- ▶ DLC Coatings is available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good


ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S							H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast iron	Hardened Cast iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○																

SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



p.30

* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49010	1.0	6	2	40
* E5E49901	1.0	6	3	50
* E5E49902	1.0	6	4	60
* E5E49903	1.0	6	5	60
* E5E49904	1.0	6	6	60
* E5E49015	1.5	6	3	40
* E5E49905	1.5	6	4	40
* E5E49906	1.5	6	5	50
* E5E49907	1.5	6	6	60
* E5E49908	1.5	6	8	60
* E5E49909	1.5	6	10	60
* E5E49020	2.0	6	3	40
* E5E49910	2.0	6	5	50
* E5E49911	2.0	6	6	50
* E5E49912	2.0	6	7	50
* E5E49913	2.0	6	8	60
* E5E49914	2.0	6	10	60

- ▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S						H				
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast iron	Hardened Cast iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○																




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49915	2.0	6	12	60
* E5E49025	2.5	6	4	40
* E5E49916	2.5	6	8	40
* E5E49917	2.5	6	10	55
* E5E49918	2.5	6	12	60
* E5E49919	2.5	6	15	60
* E5E49920	3.0	6	4	45
* E5E49921	3.0	6	8	45
* E5E49922	3.0	6	11	55
E5E49030	3.0	6	12	57
* E5E49923	3.0	6	15	65
* E5E49924	3.0	6	20	70
* E5E49925	3.0	6	25	75
* E5E49926	3.0	6	30	80
* E5E49035	3.5	6	12	55
* E5E49927	4.0	6	5	45
* E5E49928	4.0	6	8	45

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K								
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc	13	19	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21			
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommend																							
ISO	N										S						H						
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	34		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550		
Recommend	◎	◎	◎	◎	○																		


SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49929	4.0	6	11	45
* E5E49930	4.0	6	13	55
E5E49040	4.0	6	15	57
* E5E49931	4.0	6	20	70
* E5E49932	4.0	6	26	75
* E5E49933	4.0	6	30	80
* E5E49045	4.5	6	15	55
* E5E49934	5.0	6	13	50
* E5E49935	5.0	6	17	55
E5E49050	5.0	6	20	57
* E5E49936	5.0	6	22	60
* E5E49937	5.0	6	25	70
* E5E49938	5.0	6	30	75
* E5E49939	5.0	6	35	80
* E5E49940	5.0	6	40	85
* E5E49941	5.0	6	45	90
* E5E49055	5.5	6	17	55

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P											M			K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	25	28	32	36	10	29	32	38	15	35	15	23	10	10	26	3	25	21		
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S							H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	
Recommend	◎	◎	◎	◎	○																




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49942	6.0	6	13	50
* E5E49943	6.0	6	17	60
E5E49060	6.0	6	20	65
* E5E49944	6.0	6	25	70
* E5E49945	6.0	6	30	75
* E5E49946	6.0	6	35	80
* E5E49947	6.0	6	42	90
* E5E49948	6.0	6	50	100
* E5E49070	7.0	8	22	65
* E5E49949	8.0	8	19	60
E5E49080	8.0	8	22	65
* E5E49950	8.0	8	28	80
* E5E49951	8.0	8	30	80
* E5E49952	8.0	8	35	85
* E5E49953	8.0	8	40	90
* E5E49954	8.0	8	45	95
* E5E49955	8.0	8	50	100

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K								
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21				
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommend																							
ISO	N										S										H		
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	21	22	23	24	25	26	27	28	29	30	15	30	25	38	34	36	37	55	60	42	55		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550		
Recommend	◎	◎	◎	◎	○																		


SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49956	8.0	8	55	105
* E5E49957	8.0	8	60	110
* E5E49958	8.0	8	65	110
* E5E49090	9.0	10	27	70
* E5E49959	10.0	10	22	65
E5E49100	10.0	10	25	70
* E5E49960	10.0	10	32	90
* E5E49961	10.0	10	35	90
* E5E49962	10.0	10	40	90
* E5E49963	10.0	10	45	100
* E5E49964	10.0	10	50	100
* E5E49965	10.0	10	55	110
* E5E49966	10.0	10	60	110
* E5E49967	10.0	10	65	120
E5E49120	12.0	12	25	75
* E5E49968	12.0	12	30	80
* E5E49969	12.0	12	35	80

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P											M			K								
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21				
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommend																							
ISO	N										S										H		
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast iron	Hardened Cast iron		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550		
Recommend	◎	◎	◎	◎	○																		




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49970	12.0	12	40	95
* E5E49971	12.0	12	45	100
* E5E49972	12.0	12	50	100
* E5E49973	12.0	12	55	110
* E5E49974	12.0	12	60	110
* E5E49975	12.0	12	65	120
* E5E49976	12.0	12	70	120
* E5E49977	12.0	12	75	135
* E5E49978	12.0	12	80	140
* E5E49979	12.0	12	90	150
* E5E49140	14.0	14	37	90
* E5E49980	16.0	16	32	90
E5E49160	16.0	16	35	90
* E5E49981	16.0	16	45	100
* E5E49982	16.0	16	55	110
* E5E49983	16.0	16	65	130
* E5E49984	16.0	16	75	150

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K							
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron			
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20		
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21			
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230		
Recommend																						
ISO	N										S						H					
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	15	30	25	38	40	55	
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550	
Recommend	◎	◎	◎	◎	○																	


SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX LONG LENGTH

PLAIN SHANK

NEW
SIZES

E5E49 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish




* NEW SIZE

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
* E5E49985	16.0	16	85	160
* E5E49986	16.0	16	95	180
* E5E49987	16.0	16	105	190
* E5E49988	16.0	16	115	200
* E5E49180	18.0	18	48	100
E5E49200	20.0	20	40	100
* E5E49989	20.0	20	45	100
* E5E49990	20.0	20	55	110
* E5E49991	20.0	20	65	130
* E5E49992	20.0	20	75	150
* E5E49993	20.0	20	85	160
* E5E49994	20.0	20	95	180
* E5E49995	20.0	20	105	190
* E5E49996	20.0	20	115	200
* E5E49997	20.0	20	125	220

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P											M			K							
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron			
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20		
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21			
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230		
Recommend																						
ISO	N										S						H					
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast iron		Hardened Cast iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	
HRc											15	30	25	38	34			55	60	42	55	
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550	
Recommend	◎	◎	◎	◎	○																	




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX with NECK

NEW
SIZES

PLAIN SHANK

E5E50 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter
	D1	D2	L1	L3	L2	D3
* E5E50010	1.0	4	2.5	3	60	0.9
* E5E50901	1.0	4	2.5	4	60	0.9
* E5E50902	1.0	4	2.5	6	60	0.9
* E5E50903	1.0	4	2.5	8	60	0.9
* E5E50904	1.0	4	2.5	10	60	0.9
* E5E50015	1.5	4	4	6	60	1.35
* E5E50905	1.5	4	4	8	60	1.35
* E5E50906	1.5	4	4	10	60	1.35
* E5E50907	1.5	4	4	12	60	1.35
* E5E50908	1.5	4	4	16	60	1.35
* E5E50020	2.0	4	6	8	60	1.8
* E5E50909	2.0	4	6	10	60	1.8
* E5E50910	2.0	4	6	12	60	1.8
* E5E50911	2.0	4	6	16	60	1.8
* E5E50025	2.5	6	7	10	60	2.25
* E5E50912	2.5	6	7	12	60	2.25
* E5E50913	2.5	6	7	16	60	2.25

Unit : mm

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K						
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron		
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRc	13	23	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21		
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommend																					
ISO	N										S							H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	21	22	23	24	25	26	27	28	29	30	15	30	25	38	34	36	37	55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	◎	◎	◎	◎	○																


SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX with NECK

NEW
SIZES

PLAIN SHANK

E5E50 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish



* NEW SIZE


EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter
	D1	D2	L1	L3	L2	D3
* E5E50914	2.5	6	7	20	60	2.25
E5E50030	3.0	6	8	12	57	2.7
* E5E50915	3.0	6	8	16	60	2.7
* E5E50916	3.0	6	8	20	60	2.7
* E5E50917	3.0	6	8	26	70	2.7
* E5E50918	3.0	6	8	30	80	2.7
E5E50040	4.0	6	11	18	57	3.7
* E5E50919	4.0	6	11	20	60	3.7
* E5E50920	4.0	6	11	26	70	3.7
* E5E50921	4.0	6	11	30	80	3.7
E5E50050	5.0	6	13	18	57	4.7
E5E50060	6.0	6	13	18	57	5.7
* E5E50922	6.0	6	15	25	90	5.7
* E5E50923	6.0	6	15	35	90	5.7
* E5E50924	6.0	6	15	45	90	5.7
E5E50080	8.0	8	21	25	63	7.4
* E5E50925	8.0	8	21	30	100	7.4

Unit : mm

▶ DLC Coatings is available on your request.

▶ NEXT PAGE

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO	P										M				K							
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron			
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20		
HRc																						
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230		
Recommend																						
ISO	N										S						H					
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	
HRc																						
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550	
Recommend	◎	◎	◎	◎	○																	




SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE 45° HELIX with NECK

NEW SIZES

PLAIN SHANK

E5E50 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized cutting edges for increased tool life
- ▶ Mirror surface flutes for excellent chip evacuation and surface finish




* NEW SIZE

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter
	D1	D2	L1	L3	L2	D3
* E5E50926	8.0	8	21	40	100	7.4
* E5E50927	8.0	8	21	50	100	7.4
E5E50100	10.0	10	22	30	72	9.2
* E5E50928	10.0	10	25	35	100	9.2
* E5E50929	10.0	10	25	45	100	9.2
* E5E50930	10.0	10	25	55	100	9.2
E5E50120	12.0	12	26	36	83	11
* E5E50931	12.0	12	30	40	110	11
* E5E50932	12.0	12	30	50	110	11
* E5E50933	12.0	12	30	60	110	11
E5E50160	16.0	16	36	42	92	15
E5E50200	20.0	20	41	52	104	19

▶ DLC Coatings is available on your request.

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ -0.015	h5



◎ : Excellent ○ : Good

ISO Material Description	P										M			K				
	Non-alloy steel					Low alloy steel					Stainless steel			Grey cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
HRc	13	25	28	32	38	10	29	32	38	15	35	15	23	10	10	26	3	25
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250
Recommend																		
ISO Material Description	N										S					H		
	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550
Recommend	◎	◎	◎	◎	○													

SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE LONG LENGTH ROUGHING


PLAIN SHANK

E5742 SERIES

FLAT SHANK

E5711 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized geometry reducing power consumption




Unit : mm

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length	Chamfer
PLAIN	FLAT	D1(h10)	D2(h6)	L1	L2	
E5742060	E5711060	6.0	6	16	57	0.60
E5742070	E5711070	7.0	8	16	63	0.60
E5742080	E5711080	8.0	8	16	63	0.60
E5742090	E5711090	9.0	10	19	72	0.60
E5742100	E5711100	10.0	10	22	72	0.60
E5742120	E5711120	12.0	12	26	83	0.60
E5742140	E5711140	14.0	14	26	83	0.91
E5742160	E5711160	16.0	16	32	92	0.91
E5742180	E5711180	18.0	18	32	92	0.91
E5742200	E5711200	20.0	20	38	104	0.91
E5742250	E5711250	25.0	25	45	121	0.91

▶ DLC Coatings is available on your request.

Tolerances according to DIN 7160 & 7161

Tolerance range in μ m					
Nominal-Diameter in μ m					
	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30
h10	0 - 40	0 - 48	0 - 58	0 - 70	0 - 84
h5	0 - 4	0 - 5	0 - 6	0 - 8	0 - 9



Enforced Cutting Edge

◎ : Excellent ○ : Good

ISO Material Description	P										M			K				
	Non-alloy steel					Low alloy steel					Stainless steel			Grey cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
HRc	13	25	28	32	38	10	29	32	38	15	35	15	23	10	10	26	3	25
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250
Recommend																		
ISO Material Description	N										S					H		
	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550
Recommend	◎	◎	◎	◎	○													



SOLID CARBIDE ALU-POWER END MILLS CARBIDE, 3 FLUTE ROUGHING with NECK


PLAIN SHANK

E5E39 SERIES

FLAT SHANK

E5E40 SERIES

- ▶ Excellent results on aluminum and copper materials
- ▶ Optimized geometry reducing power consumption




EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Length Below Shank	Overall Length	Neck Diameter	Chamfer
PLAIN	FLAT	D1	D2	L1	L3	L2	D3	
E5E39060	E5E40060	6.0	6	16	20	57	5	0.60
E5E39080	E5E40080	8.0	8	16	25	63	7	0.60
E5E39100	E5E40100	10.0	10	22	30	72	9	0.60
E5E39120	E5E40120	12.0	12	26	36	83	10.5	0.60
E5E39160	E5E40160	16.0	16	32	42	92	14.5	0.91
E5E39200	E5E40200	20.0	20	38	52	104	18.5	0.91

Unit : mm

- ▶ DLC Coatings is available on your request.

Tolerances according to DIN 7160 & 7161

Tolerance range in μm					
Nominal-Diameter in μm					
	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30
h10	0 - 40	0 - 48	0 - 58	0 - 70	0 - 84
h5	0 - 4	0 - 5	0 - 6	0 - 8	0 - 9



Enforced Cutting Edge

ISO		P										M				K			
Material Description		Non-alloy steel					Low alloy steel					Stainless steel				Grey cast iron			
VDI 3323	HRc	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
HB		125	130	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25
Recommend																			
ISO		N										S				H			
Material Description		Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)				Heat Resistant Super Alloys			
VDI 3323	HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
HB		60	100	75	90	130	110	90	100			15	30	25	38	34	55	60	55
Recommend		◎	◎	◎	◎	○													

◎ : Excellent ○ : Good

RECOMMENDED CUTTING CONDITIONS


ALU-POWER

E5910 SERIES

2 FLUTE BALL

Vc = m/min. fz = mm/tooth
RPM = rev./min. FEED = mm/min.


ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)					
						6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	0.2D	0.5D	Vc	270	280	350	420	440	350
					fz	0.049	0.071	0.084	0.107	0.123	0.157
					RPM	14324	11141	11141	8754	5570	
					FEED	1404	1582	1872	2384	2153	1749
	23~24	Aluminum-cast, alloyed	0.2D	0.5D	Vc	176	182	228	273	286	228
					fz	0.049	0.071	0.084	0.107	0.123	0.157
					RPM	9311	7242	7242	7242	5690	3621
					FEED	912	1028	1217	1550	1400	1137
	26-28	Copper and Copper Alloys (Bronze / Brass)	0.2D	0.5D	Vc	85	85	105	125	135	105
					fz	0.04	0.06	0.069	0.089	0.101	0.131
					RPM	4509	3382	3342	3316	2686	1671
					FEED	361	406	461	590	543	438



E5908 SERIES

3 FLUTE BALL

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)											
						2.0	2.5	3.0	3.5	4.0	5.0	6.0	8.0	10.0	12.0	16.0	
N	21~22	Aluminum-wrought alloy	0.2D	0.5D	Vc	135	140	135	160	180	225	270	280	350	420	440	
					fz	0.018	0.022	0.026	0.028	0.035	0.038	0.049	0.071	0.084	0.107	0.123	
					RPM	21486	17825	14324	14551	14324	14324	14324	11141	11141	11141	8754	
	FEED	1160	1176	1117	1222	1504	1633	2106	2373	2807	3576	3230					
		23~24	Aluminum-cast, alloyed	0.2D	0.5D	Vc	88	91	88	104	117	146	176	182	228	273	286
						fz	0.018	0.022	0.026	0.028	0.035	0.038	0.049	0.071	0.084	0.107	0.123
	RPM					13966	11586	9311	9458	9311	9311	9311	7242	7242	7242	5690	
	FEED	754	765	726	795	978	1061	1369	1542	1825	2325	2100					
		26-27	Copper and Copper Alloys (Bronze / Brass)	0.2D	0.5D	Vc	40	40	40	50	55	70	85	85	105	125	135
						fz	0.015	0.018	0.022	0.022	0.028	0.031	0.04	0.06	0.069	0.089	0.101
	RPM					6366	5093	4244	4547	4377	4456	4509	3382	3342	3316	2686	
	FEED	286	275	280	300	368	414	541	609	692	885	814					




E5930 SERIES

2 FLUTE CORNER RADIUS - SLOTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						2.0	3.0	4.0	5.0	6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	65	100	130	165	195	200	250	300	320	250
					fz	0.022	0.035	0.046	0.05	0.058	0.09	0.11	0.135	0.156	0.2
					RPM	10345	10610	10345	10504	10345	7958	7958	7958	6366	3979
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	FEED	455	743	952	1050	1200	1432	1751	2149	1986	1592
					Vc	42	65	85	107	127	130	163	195	208	163
					fz	0.022	0.035	0.046	0.05	0.058	0.09	0.11	0.135	0.156	0.2
					RPM	6724	6897	6724	6828	6724	5173	5173	5173	4138	2586
					FEED	296	483	619	683	780	931	1138	1397	1291	1035

2 FLUTE CORNER RADIUS - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						2.0	3.0	4.0	5.0	6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	0.2~0.10=0.25D 0.12~0.20=0.5D	1.0D	Vc	65	100	130	165	195	200	250	300	320	250
					fz	0.039	0.046	0.054	0.065	0.077	0.115	0.135	0.170	0.194	0.250
					RPM	10345	10610	10345	10504	10345	7958	7958	7958	6366	3979
	23~24	Aluminum-cast, alloyed	0.2~0.10=0.25D 0.12~0.20=0.5D	1.0D	FEED	807	976	1117	1366	1593	1830	2149	2706	2470	1989
					Vc	42	65	85	107	127	130	163	195	208	163
					fz	0.039	0.046	0.054	0.065	0.077	0.115	0.135	0.170	0.194	0.250
					RPM	6724	6897	6724	6828	6724	5173	5173	5173	4138	2586
					FEED	524	634	726	888	1036	1190	1397	1759	1606	1293



E5909 SERIES


2 FLUTE CORNER RADIUS - SLOTting

Vc = m/min.
RPM = rev./min. fz = mm/tooth
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						4.0	6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	130	195	200	250	300	320	250
					fz	0.046	0.058	0.09	0.11	0.135	0.156	0.2
					RPM	10345	10345	7958	7958	7958	6366	3979
					FEED	952	1200	1432	1751	2149	1986	1592
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	85	127	130	163	195	208	163
					fz	0.046	0.058	0.09	0.11	0.135	0.156	0.2
					RPM	6724	6724	5173	5173	5173	4138	2586
					FEED	619	780	931	1138	1397	1291	1035
	26~28	Copper and Copper Alloys (Bronze / Brass)	1.0D	0.5D	Vc	40	60	60	75	90	95	75
					fz	0.038	0.049	0.075	0.092	0.114	0.132	0.167
					RPM	3183	3183	2387	2387	2387	1890	1194
					FEED	242	312	358	439	544	499	399

2 FLUTE CORNER RADIUS - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						4.0	6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	~Ø10=0.25D Ø12~Ø20=0.5D	1.0D	Vc	130	195	200	250	300	320	250
					fz	0.054	0.077	0.115	0.135	0.17	0.194	0.25
					RPM	10345	10345	7958	7958	7958	6366	3979
					FEED	1117	1593	1830	2149	2706	2470	1989
	23~24	Aluminum-cast, alloyed	~Ø10=0.25D Ø12~Ø20=0.5D	1.0D	Vc	85	127	130	163	195	208	163
					fz	0.054	0.077	0.115	0.135	0.17	0.194	0.25
					RPM	6724	6724	5173	5173	5173	4138	2586
					FEED	726	1036	1190	1397	1759	1606	1293
	26~28	Copper and Copper Alloys (Bronze / Brass)	~Ø10=0.25D Ø12~Ø20=0.5D	1.0D	Vc	40	60	60	75	90	95	75
					fz	0.045	0.064	0.097	0.114	0.142	0.163	0.21
					RPM	3183	3183	2387	2387	2387	1890	1194
					FEED	286	407	463	544	678	616	501




E5E51 SERIES

3 FLUTE CORNER RADIUS - SLOTting

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)							
						3.0	4.0	5.0	6.0	8.0	10.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	95	125	155	190	200	250	300	250
					fz	0.039	0.050	0.055	0.066	0.096	0.117	0.174	0.220
					RPM	10080	9947	9868	10080	7958	7958	5968	3979
					FEED	1179	1492	1628	1996	2292	2793	3462	2626
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	62	81	101	124	130	163	195	163
					fz	0.039	0.050	0.055	0.066	0.096	0.117	0.174	0.220
					RPM	6552	6466	6414	6552	5173	5173	3879	2586
					FEED	767	970	1058	1297	1490	1816	2250	1707

3 FLUTE CORNER RADIUS - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)							
						3.0	4.0	5.0	6.0	8.0	10.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	0.15D	2.5D	Vc	95	125	155	190	200	250	300	250
					fz	0.050	0.061	0.072	0.083	0.125	0.145	0.179	0.220
					RPM	10080	9947	9868	10080	7958	7958	5968	3979
					FEED	1512	1820	2131	2510	2984	3462	3939	3127
	23~24	Aluminum-cast, alloyed	0.15D	2.5D	Vc	62	81	101	124	130	163	195	163
					fz	0.050	0.061	0.072	0.083	0.125	0.145	0.179	0.220
					RPM	6552	6466	6414	6552	5173	5173	3879	2586
					FEED	983	1183	1385	1631	1940	2250	2778	2033



E5E48, E5522, E5521 SERIES


2 FLUTE - SLOTting

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)							
						1.0	1.5	2.0	2.5	3.0	4.0	5.0	6.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	53	62	71	83	95	125	155	190
					fz	0.015	0.020	0.025	0.030	0.035	0.045	0.050	0.060
					RPM	16870	13150	11300	10565	10080	9947	9868	10080
					FEED	505	525	565	635	706	895	987	1210
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	34	40	46	54	62	81	101	124
					fz	0.015	0.020	0.025	0.030	0.035	0.045	0.050	0.060
					RPM	10823	8488	7321	6875	6552	6466	6414	6552
					FEED	325	340	366	413	459	582	641	786

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						8.0	10.0	12.0	14.0	16.0	18.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	200	250	300	265	300	225	250
					fz	0.088	0.106	0.131	0.150	0.158	0.175	0.200
					RPM	7958	7958	7958	6025	5968	3979	3979
					FEED	1401	1687	2085	1808	1886	1393	1592
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	130	163	195	172	195	146	163
					fz	0.088	0.106	0.131	0.150	0.158	0.175	0.200
					RPM	5173	5173	5173	3916	3879	2586	2586
					FEED	910	1097	1355	1175	1226	905	1035

※ For long flute tools, it is recommended to adjust the conditions according to the following ratios.

Length of Cut	RPM	FEED
Up to 3D	100%	100%
Up to 5D	70%	80%
Up to 7D	Not recommended	
Over 7D		



2 FLUTE - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)							
						1.0	1.5	2.0	2.5	3.0	4.0	5.0	6.0
N	21~22	Aluminum-wrought alloy	Ø1~Ø10=0.25D Ø12~Ø20=0.5D	1.0D	Vc	53	62	71	83	95	125	155	190
					fz	0.025	0.030	0.035	0.040	0.045	0.055	0.065	0.075
					RPM	16870	13150	11300	10565	10080	9947	9868	10080
					FEED	845	790	790	845	907	1094	1283	1512
	23~24	Aluminum-cast, alloyed	Ø1~Ø10=0.25D Ø12~Ø20=0.5D	1.0D	Vc	34	40	46	54	62	81	101	124
					fz	0.015	0.020	0.025	0.030	0.045	0.055	0.065	0.075
					RPM	10823	8488	7321	6875	6552	6466	6414	6552
					FEED	325	340	366	413	590	711	834	983

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						8.0	10.0	12.0	14.0	16.0	18.0	20.0

E5E49 SERIES

3 FLUTE - SLOTTING


Vc = m/min.
RPM = rev./min. fz = mm/tooth
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	53	61	63	63	65	75	90	100	110	120
					fz	0.023	0.027	0.027	0.033	0.035	0.035	0.045	0.050	0.050	0.060
					RPM	16870	12945	10027	8021	6897	6821	7162	7074	7003	6945
					FEED	1164	1049	812	794	724	716	967	1061	1050	1250
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	34	40	41	41	42	49	59	65	72	78
					fz	0.023	0.027	0.027	0.033	0.035	0.035	0.045	0.050	0.050	0.060
					RPM	10823	8488	6525	5220	4483	4456	4655	4598	4552	4514
					FEED	747	688	529	517	471	468	628	690	683	813

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						6.0	7.0	8.0	9.0	10.0	12.0	14.0	16.0	18.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	130	130	140	160	175	210	185	210	160	175
					fz	0.060	0.081	0.088	0.097	0.106	0.131	0.150	0.158	0.173	0.200
					RPM	6897	5911	5570	5659	5570	5570	4206	4178	2829	2785
					FEED	1241	1436	1471	1647	1771	2189	1893	1980	1468	1671
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	85	85	91	104	114	137	120	137	104	114
					fz	0.060	0.081	0.088	0.097	0.106	0.131	0.150	0.158	0.173	0.200
					RPM	4483	3865	3621	3678	3621	3621	2728	2716	1839	1810
					FEED	807	939	956	1070	1151	1423	1228	1287	954	1086

※ For long flute tools, it is recommended to adjust the conditions according to the following ratios.

Length of Cut	RPM	FEED
Up to 3D	100%	100%
Up to 5D	70%	80%
Up to 7D	Not recommended	
Over 7D		




3 FLUTE - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
N	21~22	Aluminum-wrought alloy	0.15D	1.5D ~ 2.5D	Vc	53	61	63	63	65	75	90	100	110	120
					fz	0.038	0.046	0.044	0.046	0.045	0.054	0.055	0.060	0.065	0.069
					RPM	16870	12945	10027	8021	6897	6821	7162	7074	7003	6945
					FEED	1923	1786	1324	1107	931	1105	1182	1273	1366	1438
	23~24	Aluminum-cast, alloyed	0.15D	1.5D ~ 2.5D	Vc	34	40	41	41	42	49	59	65	72	78
					fz	0.038	0.046	0.044	0.046	0.045	0.054	0.055	0.060	0.065	0.069
					RPM	10823	8488	6525	5220	4483	4456	4655	4598	4552	4514
					FEED	1234	1171	861	720	605	722	768	828	888	934

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						6.0	7.0	8.0	9.0	10.0	12.0	14.0	16.0	18.0	20.0
N	21~22	Aluminum-wrought alloy	0.15D	1.5D ~ 2.5D	Vc	130	130	140	160	175	210	185	210	160	175
					fz	0.075	0.096	0.113	0.122	0.131	0.163	0.183	0.200	0.225	0.238
					RPM	6897	5911	5570	5659	5570	5570	4206	4178	2829	2785
					FEED	1552	1702	1888	2071	2189	2724	2309	2507	1910	1989
	23~24	Aluminum-cast, alloyed	0.15D	1.5D ~ 2.5D	Vc	85	85	91	104	114	137	120	137	104	114
					fz	0.075	0.096	0.113	0.122	0.131	0.163	0.183	0.200	0.225	0.238
					RPM	4483	3865	3621	3678	3621	3621	2728	2716	1839	1810
					FEED	1009	1113	1227	1346	1423	1771	1498	1629	1241	1293

※ For long flute tools, it is recommended to adjust the conditions according to the following ratios.

Length of Cut	RPM	FEED
Up to 3D	100%	100%
Up to 5D	70%	70%
Up to 7D	40%	70%
Over 7D	40%	50%



E5E50 SERIES

3 FLUTE - SLOTTING


Vc = m/min.
RPM = rev./min. fz = mm/tooth
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						1.0	1.5	2.0	2.5	3.0	4.0	5.0			
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	53	61	63	63	65	90	110			
					fz	0.023	0.027	0.027	0.033	0.035	0.045	0.050			
					RPM	16870	12945	10027	8021	6897	7162	7003			
					FEED	1164	1049	812	794	724	967	1050			
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	34	40	41	41	42	59	72			
					fz	0.023	0.027	0.027	0.033	0.035	0.045	0.050			
					RPM	10823	8488	6525	5220	4483	4655	4552			
					FEED	747	688	529	517	471	628	683			

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						6.0	8.0	9.0	10.0	12.0	16.0	20.0			
N	21~22	Aluminum-wrought alloy	1.0D	0.5D	Vc	130	140	160	175	210	210	175			
					fz	0.060	0.088	0.097	0.106	0.131	0.158	0.200			
					RPM	6897	5570	5659	5570	5570	4178	2785			
					FEED	1241	1471	1647	1771	2189	1980	1671			
	23~24	Aluminum-cast, alloyed	1.0D	0.5D	Vc	85	91	104	114	137	137	114			
					fz	0.060	0.088	0.097	0.106	0.131	0.158	0.200			
					RPM	4483	3621	3678	3621	3621	2716	1810			
					FEED	807	956	1070	1151	1423	1287	1086			

※ For long neck type tools, condition adjustments are recommended as per the ratios below.

Neck length	RPM	FEED
Up to 3D	100%	100%
Over 3D ~ Up to 5D	70%	70%
Over 5D	50%	50%



3 FLUTE - SIDE CUTTING

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)									
						1.0	1.5	2.0	2.5	3.0	4.0	5.0			
N	21~22	Aluminum-wrought alloy	0.15D	1.5D ~ 2.5D	Vc	53	61	63	63	65	90	110			
					fz	0.038	0.046	0.044	0.046	0.045	0.055	0.065			
					RPM	16870	12945	10027	8021	6897	7162	7003			
					FEED	1923	1786	1324	1107	931	1182	1366			
	23~24	Aluminum-cast, alloyed	0.15D	1.5D ~ 2.5D	Vc	34	40	41	41	42	59	72			
					fz	0.038	0.046	0.044	0.046	0.045	0.055	0.065			
					RPM	10823	8488	6525	5220	4483	4655	4552			
					FEED	1234	1171	861	720	605	768	888			


ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)						
						6.0	8.0	9.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	0.15D	1.5D ~ 2.5D	Vc	130	140	160	175	210	210	175
						0.075	0.113	0.122	0.131	0.163	0.200	0.238
					RPM	6897	5570	5659	5570	5570	4178	2785
					FEED	1552	1888	2071	2189	2724	2507	1989
	23~24	Aluminum-cast, alloyed	0.15D	1.5D ~ 2.5D	Vc	85	91	104	114	137	137	114
					fz	0.075	0.113	0.122	0.131	0.163	0.200	0.238
					RPM	4483	3621	3678	3621	3621	2716	1810
					FEED	1009	1227	1346	1423	1771	1629	1293

E5E47 SERIES

1 FLUTE - **SLOTING**

Vc = m/min.
RPM = rev./min. fz = mm/tooth
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)							
						2.0	3.0	4.0	5.0	6.0	8.0	10.0	12.0
N	21~22	Aluminum-wrought alloy	1.0D	1.5D	Vc	145	170	190	190	190	195	190	190
					fz	0.065	0.094	0.120	0.150	0.180	0.244	0.333	0.440
					RPM	23077	18038	15120	12096	10080	7759	6048	5040
					FEED	1500	1696	1814	1814	1893	2014	2218	2218
	23~24	Aluminum-cast, alloyed	1.0D	1.5D	Vc	94	111	124	124	124	127	124	124
					fz	0.065	0.094	0.120	0.150	0.180	0.244	0.333	0.440
					RPM	15000	11724	9828	7862	6552	5043	3931	3276
					FEED	975	1102	1179	1179	1179	1231	1309	1441
	29.1	Non Metallic Materials (Duroplastic)	1.0D	1.5D	Vc	200	235	250	235	255	250	250	255
					fz	0.069	0.096	0.120	0.147	0.170	0.240	0.300	0.343
					RPM	31831	24934	19894	14961	13528	9947	7958	6764
					FEED	2196	2394	2387	2199	2300	2387	2387	2320




E5742, E5711, E5E39, E5E40 SERIES

3 FLUTE ROUGHING - **SLOTING**

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)					
						6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	1.0D	1.5D	Vc	198	201	204	241	241	242
					fz	0.168	0.167	0.179	0.167	0.167	0.165
					RPM	10504	7998	6494	6393	4795	3852
					FEED	5294	4007	3487	3203	2402	1907
	23~24	Aluminum-cast, alloyed	1.0D	1.5D	Vc	129	131	133	157	157	157
					fz	0.168	0.167	0.179	0.167	0.167	0.165
					RPM	6828	5198	4221	4155	3116	2504
					FEED	3441	2604	2267	2082	1561	1239

3 FLUTE ROUGHING - **SIDE CUTTING**

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)					
						6.0	8.0	10.0	12.0	16.0	20.0
N	21~22	Aluminum-wrought alloy	0.5D	1.5D	Vc	254	264	267	320	322	320
					fz	0.168	0.168	0.169	0.165	0.167	0.163
					RPM	13475	10504	8499	8488	6406	5093
					FEED	6791	5294	4309	4202	3209	2490
	23~24	Aluminum-cast, alloyed	0.5D	1.5D	Vc	165	172	174	208	209	208
					fz	0.168	0.168	0.169	0.165	0.167	0.163
					RPM	8759	6828	5524	5517	4164	3310
					FEED	4414	3441	2801	2731	2086	1619



MEMO



MEMO



HIGH QUALITY PRODUCTS and ON TIME DELIVERY for WORLD-WIDE CUSTOMERS

Since 1982, YG-1 has been committed to quality, innovation and the unique customer experience. Our performance and experience have granted YG-1 the global impression of one of the leading manufacturers of high quality cutting tool solutions. This global footprint expands over 75 countries, with international logistic centers, pledging to our customers to give the best service available today - and tomorrow.

EUROPE

 BELGIUM	 FINLAND	 ITALY	 PORTUGAL	 SLOVENIA	 THE NETHERLANDS
 CROATIA	 FRANCE	 LITHUANIA	 ROMANIA	 SPAIN	 TÜRKIYE
 CZECH REPUBLIC	 GERMANY	 NORWAY	 SWEDEN	 UNITED KINGDOM	 DENMARK
 HUNGARY	 POLAND	 SERBIA	 SWITZERLAND	 AUSTRIA	 GREECE
 ALBANIA	 BOSNIA AND HERZEGOVINA	 UKRAINE	 UZBEKISTAN	 BULGARIA	
 ESTONIA					

ASIA PACIFIC

 AUSTRALIA	 INDONESIA	 MALAYSIA	 SOUTH KOREA	 VIETNAM
 CHINA	 ISRAEL	 PAKISTAN	 TAIWAN	
 HONG KONG	 JAPAN	 PHILIPPINES	 THAILAND	
 INDIA	 SAUDI ARABIA	 SINGAPORE	 UNITED ARAB EMIRATES	

AMERICAS

 BRAZIL	 CANADA	 COLOMBIA	 MEXICO	 UNITED STATES
--	--	--	--	---

AFRICA

 EGYPT	 SOUTH AFRICA
---	--

YG-1 CO., LTD.

* For the more information on sales network, please contact the head office as below;

HEAD OFFICE

13-40, Songdogwahak-ro 16beon-gil, Yeonsu-gu, Incheon 21984, South Korea

Phone: +82-32-526-0909

www.yg1.solutions

E-mail: yg1@yg1.solutions